



SAFETY DATA SHEET

A00028

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name A00028
Product number A00028,FP-000029,FP-000034,FP-000037

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier APOLLO CHEMICALS LTD
 SANDY WAY
 AMINGTON INDUSTRIAL ESTATE
 TAMWORTH
 STAFFS
 B77 4DS
 T: +44 (0) 1827 54281
 F: +44 (0) 1827 53030
 E: sds@apolloadhesives.com

1.4. Emergency telephone number

Emergency telephone +44 01827 69662 (NOT 24HRS)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 - H336
 STOT RE 2 - H373
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xn;R48/20. Repr. Cat. 3;R63. Xi;R38. F;R11. N;R51/53. R67.

Physicochemical The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

2.2. Label elements

A00028**Pictogram****Signal word**

Danger

Hazard statements

H315 Causes skin irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H361d Suspected of damaging the unborn child.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H225 Highly flammable liquid and vapour.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapour/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P501 Dispose of contents/container in accordance with national regulations.

Supplemental label information

RCH002a Restricted to professional users.

Contains

TOLUENE, hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane, BUTANONE, ACETONE, ROSIN

A00028**Supplementary precautionary statements**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P314 Get medical advice/attention if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P391 Collect spillage.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

TOLUENE		30-60%
CAS number: 108-88-3	EC number: 203-625-9	REACH registration number: 01-2119471310-51-0051
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67	
Acute Tox. 4 - H302		
Acute Tox. 4 - H312		
Skin Irrit. 2 - H315		
Repr. 2 - H361d		
STOT SE 3 - H336		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		

A00028

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane			10-30%
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411		Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
BUTANONE			5-10%
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		F;R11 Xi;R36 R66 R67	
ACETONE			5-10%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225 Acute Tox. 4 - H312 Eye Irrit. 2 - H319 STOT SE 3 - H336		F;R11 Xi;R36 R66 R67	
ROSIN			1-5%
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-0036	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Skin Sens. 1 - H317		R43	

A00028

HEXANE-norm		<1%
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67	
Skin Irrit. 2 - H315	N;R51/53	
Repr. 2 - H361f		
STOT SE 3 - H336		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

General information	Get medical attention if any discomfort continues.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is flammable. Heating may generate flammable vapours. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . The product is highly flammable.
-------------------------	---

A00028

Hazardous combustion products Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.

Special protective equipment for firefighters Wear chemical protective suit.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Usage precautions Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection**8.1. Control parameters****Occupational exposure limits****TOLUENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m³(Sk)

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m³(Sk)

A00028**ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

TOLUENE (CAS: 108-88-3)

DNEL Workers - Inhalation; Short term systemic effects: mg/m³

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Ingredient comments WEL = Workplace Exposure Limits

ACETONE (CAS: 67-64-1)

Ingredient comments WEL = Workplace Exposure Limits

BUTANONE (CAS: 78-93-3)

Ingredient comments WEL = Workplace Exposure Limits

Biological limit values Short Term Value: 300ppm Long Term Value: 200ppm

8.2. Exposure controls**Protective equipment****Appropriate engineering controls**

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P3. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

A00028

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties
--

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Various colours.
Odour	Characteristic.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not determined.
Flash point	-35°C
Evaporation rate	Not determined.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.6 Upper flammable/explosive limit: 13
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.86 @ 20°C
Bulk density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	200°C
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No information required.
Refractive index	Not available.

A00028

Particle size	Not available.
Molecular weight	Not available.
Volatility	Not available.
Saturation concentration	Not available.
Critical temperature	Not available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity - oral**

ATE oral (mg/kg) 4,545.45

Acute toxicity - dermal

ATE dermal (mg/kg) 4,545.45

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 400.0

Toxicological information on ingredients.**TOLUENE****Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

ATE oral (mg/kg) 2,000.0

Acute toxicity - dermal

A00028

Acute toxicity dermal (LD₅₀ 2,000.0 mg/kg)

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20.0

Species Rat

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 20.0

Species Rat

ATE inhalation (vapours mg/l) 20.0

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Toxicological effects No information available.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

Notes (oral LD₅₀) Not known. Data lacking.

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,920.0

Species Rat

Notes (dermal LD₅₀) Data lacking.

ATE dermal (mg/kg) 2,920.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 25.2

Species Rat

ATE inhalation (vapours mg/l) 25.2

Skin corrosion/irritation

Animal data Data lacking.

Serious eye damage/irritation

A00028

Serious eye damage/irritation	Data lacking.
<u>Aspiration hazard</u>	
Aspiration hazard	Kinematic viscosity > 20.5 mm ² /s.
Inhalation	May cause respiratory system irritation.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Irritating to skin.
Eye contact	May cause severe eye irritation.
Acute and chronic health hazards	Vapour from this product may be hazardous by inhalation.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact
Target organs	No specific target organs known.
Medical symptoms	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
Medical considerations	No information available.

BUTANONE**Acute toxicity - oral**

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 20.0

Species Rat

ACETONE

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

A00028

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 76.0

Species Rat

ATE inhalation (vapours mg/l) 76.0

Skin corrosion/irritation

Extreme pH Slightly irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

SECTION 12: Ecological Information**Ecological information on ingredients.****hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Ecotoxicity Dangerous for the environment.

12.1. Toxicity**Ecological information on ingredients.****TOLUENE**

Acute toxicity - fish , 48 hours, 48 hours: > 1-10 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 11.5 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 100 mg/l, Algae

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute toxicity - fish LC₅₀, hours: >1-<10 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3 mg/l, Daphnia magna

A00028

Acute toxicity - aquatic plants LC₀, hours: >1-<10 mg/l, Algae

BUTANONE

Acute toxicity - fish LC₅₀, EC₅₀, IC₅₀, : 100 mg/l, Fish

Acute toxicity - aquatic plants LC₅₀, EC₅₀, IC₅₀, : 100 mg/l, Algae

ACETONE

Toxicity Not considered toxic to fish.

Acute toxicity - fish LC₅₀, 96 hours, 96 hours: 5540 mg/l, Freshwater fish
, 96 hours, 96 hours: 11000 mg/l, Marinewater fish
LC₅₀, 96 hours: 11000 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours, 48 hours: 8800 mg/l, Daphnia magna
EC₅₀, 48 hours: 8800 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 430 mg/l, Algae

Acute toxicity - microorganisms , 30 min, 30 minutes: 1000 mg/l, Activated sludge

HEXANE-norm

Acute toxicity - fish LC₅₀, EC₅₀, IC₅₀, : 10 mg/l, Fish

Acute toxicity - aquatic invertebrates LC₅₀, EC₅₀, IC₅₀, : 10 mg/l, Daphnia magna

Acute toxicity - aquatic plants LC₅₀, EC₅₀, IC₅₀, : 10 mg/l, Algae

12.2. Persistence and degradability**Ecological information on ingredients.****ACETONE**

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Partition coefficient Not available.

Ecological information on ingredients.**TOLUENE**

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Not available.

ACETONE

A00028

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.
BCF: 3,

Partition coefficient Pow: < -0.24

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.**TOLUENE**

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

BUTANONE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

ACETONE

Mobility The product is miscible with water and may spread in water systems.

Adsorption/desorption coefficient Soil - log Koc: 1.5 @ 20°C

Henry's law constant 2929-3070 Pa m³/mol @ 25°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.**TOLUENE**

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

BUTANONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

ACETONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.**TOLUENE**

A00028

Other adverse effects Not known.

BUTANONE

Other adverse effects None known.

ACETONE

Other adverse effects Not applicable.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information**14.1. UN number**

UN No. (ADR/RID) 1133
UN No. (IMDG) 1133
UN No. (ICAO) 1133
UN No. (ADN) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3
ADR/RID classification code F1
ADR/RID label 3
IMDG class 3
ICAO class/division 3
ADN class 3

Transport labels**14.4. Packing group**

A00028

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards**Environmentally hazardous substance/marine pollutant**

No.

14.6. Special precautions for user

EmS	F-E, S-D
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by	Compliance
Revision date	29/09/2015
Revision	20

A00028**Risk phrases in full**

R11 Highly flammable.
R36 Irritating to eyes.
R38 Irritating to skin.
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62 Possible risk of impaired fertility.
R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Store Between

Store Between 5°C - 25°C

Contains SVHC

NO