

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
1/15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Acetylene, dissolved

Trade name: Acetylene

Additional identification

Chemical name: acetylene (ethyne)

Chemical formula: C₂H₂

INDEX No. 601-015-00-0

CAS-No. 74-86-2

EC No. 200-816-9

REACH Registration No. 01-2119457406-36-0041

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Fuel gas for welding, cutting, heating, brazing and soldering applications. Use as a fuel. Use for electronic component manufacture. Using gas alone or in mixtures for the calibration of analysis equipment. Using gas as feedstock in chemical processes. Formulation of mixtures with gas in pressure receptacles. Metal coating by spray gun. Lubrication of moulds for the manufacture of glass bottles.
Consumer use.
Fuel gas for welding, cutting, heating, brazing and soldering applications.

Uses advised against

1.3 Details of the supplier of the safety data sheet

Supplier

BOC
Priestley Road, Worsley
M28 2UT Manchester

Telephone: 0800 111 333

E-mail: ReachSDS@boc.com

1.4 Emergency telephone number: 0800 111 333

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
2/15

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.

F+; R12 R5 R6

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Dissolved gas	H280: Contains gas under pressure; may explode if heated.
Chemically unstable gases	Category A	H230: May react explosively even in the absence of air.

2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H220: Extremely flammable gas.
H230: May react explosively even in the absence of air.
H280: Contains gas under pressure; may explode if heated.

Precautionary Statement

Prevention: P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response: P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381: Eliminate all ignition sources if safe to do so.

Storage: P403: Store in a well-ventilated place.

Disposal: P501: Dispose of cylinder via gas supplier only; cylinder contains a porous material which in some cases contains asbestos.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
3/15

2.3 Other hazards: For safety reasons, acetylene is dissolved in a solvent, either acetone (CAS No, 67-64-1) or N,N-dimethylformamide (DMF) (CAS No. 68-12-2). A small quantity of the solvent (as an impurity) may be carried over with the acetylene as it is used. The concentration of the solvent in the gas is below the limit which could affect the classification of the acetylene.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	acetylene (ethyne)
INDEX No.:	601-015-00-0
CAS-No.:	74-86-2
EC No.:	200-816-9
REACH Registration No.:	01-2119457406-36-0041
Purity:	100 % The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	Acetylene

SECTION 4: First Aid Measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Adverse effects not expected from this product.

Skin Contact: Adverse effects not expected from this product.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
4/15

SECTION 5: Firefighting Measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water Spray or Fog. Dry powder. Foam.

Unsuitable extinguishing media: Carbon dioxide.

5.2 Special hazards arising from the substance or mixture:

Fire or excessive heat may produce hazardous decomposition products. When involved in a fire, acetylene can begin to decompose, breaking down into its constituent elements of hydrogen and carbon. The decomposition reaction is exothermic and produces heat. Acetylene cylinders are designed to contain and inhibit decomposition of acetylene, however, if left unchecked decomposition could lead to cylinder failure. Acetylene may continue to be a hazard after a external fire has been extinguished, due to the decomposition of the acetylene within the cylinder, and requires specific operational procedures.

Hazardous Combustion Products:

If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: carbon monoxide

5.3 Advice for firefighters

Special fire fighting procedures:

In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive re-ignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out. Acetylene cylinders that have been heated, damaged by fire or subjected to a flash back must not be moved until it has been demonstrated that there is no decomposition of the acetylene within the cylinder. Acetylene cylinders should be cooled with a water spray and a hazard zone designated around them. Water cooling should be continued for at least one hour. After a minimum of one hour of water cooling the cylinder's temperature should be checked to see if it has been effectively cooled. Effectively cooled means bringing the cylinder shell temperature down to ambient temperature. The "Wetting test" and/or thermal imaging equipment should be used to ascertain if the cylinder shell has been effectively cooled. When effective cooling of the cylinder shell has been achieved, water cooling should be stopped. The cylinder should still not be moved for a further one hour, during this time temperature checks of the cylinder shell should be made every 15 minutes. If any increase in temperature is observed a further one hour continuous water cooling should be applied to the cylinder before its temperature is re-checked. When the cylinder shell temperature remains at ambient temperature for one hour without being water cooled, and is not leaking, the cylinder may be moved.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
5/15

Special protective equipment for firefighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. Eliminate all ignition sources if safe to do so. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition.

6.4 Reference to other sections:

Refer to sections 8 and 13.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
6/15

SECTION 7: Handling and Storage:

- 7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use only non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place. Avoid suckback of water, acid and alkalis. Solvent may accumulate in piping systems. For maintenance use appropriately chemically resistant gloves and goggles. Only equipment fitted with suitable means of preventing a 'flash back' should be fitted to the cylinders. Mechanical shock alone to a cold acetylene cylinder cannot initiate decomposition. For further information on safe use refer to EIGA "Code of Practice: Acetylene" IGC Doc 123.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
7/15

7.2 Conditions for safe storage, including any incompatibilities: All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material. Acetylene cylinders should be stored vertically. If a cylinder has been transported horizontally, it should be stood upright for a minimum of 1 hour prior to use. This will allow the acetone to evenly re-distribute within the cylinder and prevent acetone being carried into the flame during use causing a 'flame thrower' effect.

7.3 Specific end use(s): None.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

DNEL-Values

Critical component	type	Value	Remarks
acetylene (ethyne)	Worker - inhalative, long-term - systemic	2500 ppm	-
	Worker - inhalative, short-term - systemic	2500 ppm	-

PNEC-Values

Critical component	type	Value	Remarks
acetylene (ethyne)			PNEC not available.

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Use only permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
8/15

Individual protection measures, such as personal protective equipment

General information:	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.
Eye/face protection:	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection	
Hand Protection:	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks.
Body protection:	Wear fire/flare resistant/retardant clothing. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	Not required.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13.

SECTION 9: Physical And Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Dissolved gas
Colour:	Colourless
Odour:	Garlic-like odour
Odour Threshold:	Odour threshold is subjective and is inadequate to warn of over exposure.
pH:	not applicable.
Melting Point:	-80.7 °C
Boiling Point:	-84.7 °C (101.3 hPa)

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
9/15

Sublimation Point:	not applicable.
Critical Temp. (°C):	35.0 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Flammable Gas
Flammability limit - upper (%)-:	99.99 %(V)
Flammability limit - lower(%)-:	2.3 %(V)
Vapour pressure:	698.5968 kPa (25 °C)
Vapour density (air=1):	0.91 AIR=1
Relative density:	0.6208 (-82 °C) 4 °C
Solubility(ies)	
Solubility in Water:	1,200 mg/l (25 °C)
Partition coefficient (n-octanol/water):	0.37
Autoignition Temperature:	305 °C
Decomposition Temperature:	635 °C
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0.011 mPa.s
Explosive properties:	Not applicable.
Oxidising Properties:	not applicable.

9.2 Other information: None.

Molecular weight: 26.02 g/mol (C₂H₂)

SECTION 10: Stability and Reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of Hazardous Reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants. Forms explosive acetylides with copper, silver and mercury. Do not use alloys containing more than 65% copper.
10.4 Conditions to Avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. High temperature High pressure May decompose violently at high temperature and/or pressure or in the presence of a catalyst.
10.5 Incompatible Materials:	Air and oxidisers. For material compatibility see latest version of ISO-11114. Avoid contact with pure copper, mercury, silver and brass with greater than 65% copper. Do not use alloys containing more than 43% silver. For further information on safe use refer to EIGA "Code of Practice: Acetylene" IGC Doc 123.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
10/15

10.6 Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: The following decomposition products may be produced: carbon monoxide

SECTION 11: Toxicological Information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation Product

acetylene (ethyne) LOEC: 100000 ppm

Skin Corrosion/Irritation Product Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation Product Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitisation Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity Product Based on available data, the classification criteria are not met.

Carcinogenicity Product Based on available data, the classification criteria are not met.

Reproductive toxicity Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure Product Based on available data, the classification criteria are not met.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
11/15

Aspiration Hazard
Product

Not applicable to gases and gas mixtures..

SECTION 12: Ecological Information

12.1 Toxicity

Acute toxicity
Product

No ecological damage caused by this product.

Acute toxicity - Fish
acetylene (ethyne)

LC 50 (Various, 96 h): 545 mg/l Remarks: QSAR

Acute toxicity - Aquatic Invertebrates
acetylene (ethyne)

EC 50 (Water flea (Daphnia magna), 48 h): 242 mg/l

Toxicity to microorganisms
acetylene (ethyne)

EC 50 (Alga, 72 h): 57 mg/l

12.2 Persistence and Degradability
Product

Not applicable to gases and gas mixtures..

12.3 Bioaccumulative Potential
Product

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

12.4 Mobility in Soil
Product

Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5 Results of PBT and vPvB
assessment
Product

Not classified as PBT or vPvB.

12.6 Other Adverse Effects:

No ecological damage caused by this product.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

General information:

Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Dispose of cylinder via gas supplier only; cylinder contains a porous material which in some cases contains asbestos.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
12/15

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container: 16 05 04*: gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport Information

ADR

14.1 UN Number: UN 1001
14.2 UN Proper Shipping Name: ACETYLENE, DISSOLVED
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.1
Hazard No. (ADR): 239
Tunnel restriction code: (B/D)
Emergency Action Code: 2SE
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1001
14.2 UN Proper Shipping Name: ACETYLENE, DISSOLVED
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.1
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 1001
14.2 UN Proper Shipping Name: ACETYLENE, DISSOLVED
14.3 Transport Hazard Class(es)
Class: 2.1
Label(s): 2.1
EmS No.: F-D, S-U
14.3 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
13/15

IATA

14.1 UN Number: UN 1001
14.2 Proper Shipping Name: Acetylene, dissolved
14.3 Transport Hazard Class(es):
Class: 2.1
Label(s): 2.1
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -
Other information
Passenger and cargo aircraft: Forbidden.
Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
acetylene (ethyne)	74-86-2	

Directive 96/82/EC (Seveso II): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
acetylene (ethyne)	74-86-2	100 %

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
acetylene (ethyne)	74-86-2	100 %

National Regulations

Dangerous Substances and Explosive Atmospheres Regulations (DSEAR 2002 No. 2776). Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013
Last revised date: 29.06.2015

Version: 1.0

SDS No.: 000010021936
14/15

Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations (EPS, 1996 No. 192). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010. THE ACETYLENE SAFETY (ENGLAND AND WALES AND SCOTLAND) REGULATIONS 2014 No. 1639

15.2 Chemical safety assessment:

CSA has been carried out.

SECTION 16: Other Information

Revision Information:

Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.
International Programme on Chemical Safety (<http://www.inchem.org/>)
ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
Matheson Gas Data Book, 7th Edition.
National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
The European Chemical Industry Council (CEFIC) ERICards.
United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
Substance specific information from suppliers.
Details given in this document are believed to be correct at the time of publication.
EH40 (as amended) Workplace exposure limits.

Wording of the R-phrases and H-statements in sections 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
R5	Heating may cause an explosion.
R6	Explosive with or without contact with air.
R12	Extremely flammable.

SAFETY DATA SHEET
Acetylene, dissolved

Issue Date: 10.07.2013 Version: 1.0 SDS No.: 000010021936
Last revised date: 29.06.2015 15/15

Training information: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1, H220
Press. Gas Diss. Gas, H280
Chem. Unst. Gas A, H230

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Note: When the Product Name appears in the SDS header the decimal sign and its position comply with rules for the structure and drafting of international standards, and is a comma on the line. As an example 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

Last revised date: 29.06.2015

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.